



RefTec

INTERNATIONAL SYSTEMS LLC



PhotoRoom

A2L Lite Evac Cart Mount Recovery Unit

Portable High Speed Recovery of A2L Refrigerants
(R-32,R-454B,R-454C,R-1234yf, R-1234ze) & Standard High Pressure Refrigerants

SPECIFICATIONS

Push/Pull Rates (R410a)	65-lbs/min
Vapor Rates (R410a)	1.75-lbs/min
Dimensions (l x w x h in inches)	23-3/4" X 28-1/4" X 46"
Float Connection	3-pin BH
Connections	1/2" flare
Low Pressure Switch	15" Hg
Liquid and Vapor ports:	1/2" threaded connect

A2L Lite Evac Recovery Unit

High Speed, High Efficiency Recovery of A2L & High Pressure Refrigerants

- Fast and portable unit for high pressure refrigerants
- Unit is mounted in a solid lightweight aluminum frame
- For use with medium-large tonnage chillers
- 2 large tires for ease of mobility
- R410a rated
- Lightweight commercial unit at only 161lbs
- 80% tank full float switch and 12' cable
- Air cooled unit
- Heavy duty lift handles
- UL certified

Certifications Certified by Intertek to UL-1963 standards

Order Number	Specifications
LRH-HT-A-115-A2L	115V/60HZ/1PH/20A, 110V/50HZ/1PH/20A
LRH-HT-A-240-A2L	230V/60HZ/1PH/20A, 220V/50HZ/1PH/20A

INCLUDED

2- 30cu. Inch Filter Driers
80% Tank Float Cable (12ft)
50ft. Power Cord

Optional Accessories

050-010-LRH Hose Kit consisting of (2) 10' and (1) 20' hoses, all 1/2" diameter
LRHWCK Water Cooled Condenser Kit for additional Vapor Recovery

Prodotto da:

RefTec International, Inc.
10530 Portal Crossing W
Suite 104 Bradenton
FL 34211

Tel: +1 800-214-4883
Fax: +1 941-750-0222
email: sales@reftec.com
web: www.reftec.com

Distribuito da:



TDM srl
Via Fabio Filzi, 3 - 20822 Seveso (MB)
tel +39 0362 1794873
mail: info@tdm-srl.it - web: www.tdm-srl.it