



RefTec
INTERNATIONAL SYSTEMS LLC



Evac/ASME Packaged Recovery Unit

Able to recover R134a at 303lbs/minute push/pull, 5.78lbs/minute vapor

SPECIFICATIONS

Push/Pull Rates (R134a)	303-lbs/min
Vapor Rates (R134a)	5.78-lbs/min
Dimensions (l x w x h in inches)	32x29x45
Float Connection	3-pin BH
Connections	3/4" flare
Low Pressure Switch	15" Hg
Liquid and Vapor ports:	3/4" threaded connect

Evac/ASME Tank Mount

High Speed, High Efficiency Recovery and storage of all High Pressure Refrigerants

- Packaged recovery/storage unit for high pressure refrigerants
- Unit is hard piped and permanently mounted on ASME tank
- For use with large tonnage chillers
- Capable of storing up to 6448lbs of R134a at 80% capacity
- Dual 250-psi relief valves on diverting valve
- Mounted on casters for mobility
- 80% tank full float switch and 12' cable
- Bottom drain connection
- 3 Phase models require 115V power to controls
- ETL certified

Certifications Certified by ETL to UL-1963 standards

Rated in accordance with ARI Standard 740-1998 (for R22. R134a rating pending approval)

Order Number	Specifications	Tank/gal	Weight	Condensor
CRH-A-230-1-250	230/60/1, 220/50/1, 3hp, 15A	250	2225	AIR
CRH-A-230-3-250	230/60/3, 220/50/3, 3hp, 20a	250	2225	AIR
CRH-A-460-3-250	460/60/3, 415/50/3, 3hp, 15A	250	2225	AIR
CRH-W-230-1-250	230/60/1, 220/50/1, 3hp, 15A	250	2225	AIR/WATER
CRH-W-230-3-250	230/60/3, 220/50/3, 3hp, 20a	250	2225	AIR/WATER
CRH-W-460-3-250	460/60/3, 415/50/3, 3hp, 15A	250	2225	AIR/WATER
CRH-A-230-1-500	230/60/1, 220/50/1, 3hp, 15A	500	2450	AIR
CRH-A-230-3-500	230/60/3, 220/50/3, 3hp, 20a	500	2050	AIR
CRH-A-460-3-500	460/60/3, 415/50/3, 3hp, 15A	500	2450	AIR
CRH-W-230-1-500	230/60/1, 220/50/1, 3hp, 15A	500	2450	AIR/WATER
CRH-W-230-3-500	230/60/3, 220/50/3, 3hp, 20a	500	2450	AIR/WATER
CRH-W-460-3-500	460/60/3, 415/50/3, 3hp, 15A	500	2450	AIR/WATER
CRH-A-230-1-850	230/60/1, 220/50/1, 3hp, 15A	850	2950	AIR
CRH-A-230-3-850	230/60/3, 220/50/3, 3hp, 20a	850	2950	AIR
CRH-A-460-3-850	460/60/3, 415/50/3, 3hp, 15A	850	2950	AIR
CRH-W-230-1-850	230/60/1, 220/50/1, 3hp, 15A	850	2950	AIR/WATER
CRH-W-230-3-850	230/60/3, 220/50/3, 3hp, 20a	850	2950	AIR/WATER
CRH-W-460-3-850	460/60/3, 415/50/3, 3hp, 15A	850	2950	AIR/WATER
CRH-A-230-1-1000	230/60/1, 220/50/1, 3hp, 15A	1000	2950	AIR
CRH-A-230-3-1000	230/60/3, 220/50/3, 3hp, 20a	1000	3450	AIR
CRH-A-460-3-1000	460/60/3, 415/50/3, 3hp, 15A	1000	3450	AIR
CRH-W-230-1-1000	230/60/1, 220/50/1, 3hp, 15A	1000	3450	AIR/WATER
CRH-W-230-3-1000	230/60/3, 220/50/3, 3hp, 20a	1000	3450	AIR/WATER
CRH-W-460-3-1000	460/60/3, 415/50/3, 3hp, 15A	1000	3450	AIR/WATER

INCLUDED

- One 48cu" filter core
- One 10' x 3/4" diameter hose
- Two 20' x 3/4" diameter hoses
- 50' power cord for controls
- 50' power cord for unit
- 12' tank float cable
- Two each 3/4"-5/8" and 5/8"-1/2" reducing fittings

Prodotto da:

RefTec International, Inc.
10530 Portal Crossing W
Suite 104 Bradenton
FL 34211

Tel: +1 800-214-4883
Fax: +1 941-750-0222
email: sales@reftec.com
web: www.reftec.com

Distribuito da:



TDM srl
Via Fabio Filzi, 3 - 20822 Seveso (MB)
tel +39 0362 1794873
mail: info@tdm-srl.it - web: www.tdm-srl.it