



LOVAC ASME Packaged Recovery Unit

SPECIFICATIONS



Push/Pull Rates	(R11)	100-lbs/min
	(R123)	92 -lbs/min
Vapor Rates	(R11)	.66 -lbs/min
	(R123)	.58 -lbs/min
Float Connection		3-pin BH
Connections		3/4" flare
Low Pressure Switch		29" Hg
Liquid and Vapor ports:		3/4" threaded connect

Lovac ASME Tank Mount

High Speed, High Efficiency Recovery, Vacuum and Storage of All Low Pressure Refrigerants

- Packaged recovery/ storage unit for Low pressure refrigerants
- Unit is hard piped and permanently mounted on ASME tank
- Capable of storing up to 7868lbs of R11 at 80% capacity (larger tanks available)
- Dual 250-psi relief valves on diverting valve
- Mounted on heavy duty casters for mobility
- 80% tank full float switch and 12' cable
- Bottom drain connection
- Liquid and Vapor ports: 3/4" threaded connection with isolation ball valves

Order Number	Specifications	Tank/gal	Weight	Dims
CRL-115-A-120	103-127V,50/60Hz,1Ph,1Hp,20A	120	1850lbs	68"x30"x54"
CRL-115-A-250	103-127V,50/60Hz,1Ph,1Hp,20A	250	2050lbs	94"x38"x70"
CRL-115-A-500	103-127V,50/60Hz,1Ph,1Hp,20A	500	2275lbs	117"x43"x75"
CRL-115-A-850	103-127V,50/60Hz,1Ph,1Hp,20A	850	2875lbs	166"x48"x75"
CRL-115-A-1000	103-127V,50/60Hz,1Ph,1Hp,20A	1000	3585lbs	204"x48"x75"
CRL-240-A-120	220-240V,50/60Hz,1Ph,1Hp,15A	120	1850lbs	68"x30"x54"
CRL-240-A-250	220-240V,50/60Hz,1Ph,1Hp,15A	250	2050lbs	94"x38"x70"
CRL-240-A-500	220-240V,50/60Hz,1Ph,1Hp,15A	500	2275lbs	117"x43"x75"
CRL-240-A-850	220-240V,50/60Hz,1Ph,1Hp,15A	850	2875lbs	166"x48"x75"
CRL-240-A-1000	220-240V,50/60Hz,1Ph,1Hp,15A	1000	3585lbs	204"x48"x75"

INCLUDED

One 48cu" filter core	Two 20' x 3/4" diameter hose
100' power cord for controls	One 10' x 3/4" diameter hoses
50' power cord for unit	12' tank float cable
Two each 3/4"-5/8" and 5/8"-1/2" reducing fittings	

OPTIONS

KIT001 Quick connect kit for hoses

Prodotto da:

RefTec International, Inc.
10530 Portal Crossing W
Suite 104 Bradenton
FL 34211

Tel: +1 800-214-4883
Fax: +1 941-750-0222
email: sales@reftec.com
web: www.reftec.com

Distribuito da:



TDM srl
Via Fabio Filzi, 3 - 20822 Seveso (MB)
tel +39 0362 1794873
mail: info@tdm-srl.it - web: www.tdm-srl.it